



US Army Corps
of Engineers
Construction Engineering
Research Laboratory

USA-CERL

2

TECHNICAL REPORT N-60
February 1986


AD-A166 490

Acoustic Directivity Patterns for Army Weapons Supplement 4: The Multiple Launch Rocket System

by
Paul D. Schomer

Environmental noise emissions of the Multiple Launch Rocket System (MLRS) weapon were measured in order to develop acoustic directivity patterns. Ignition noise was analyzed using C-weighting and separated from rocket engine noise, which was analyzed using A-weighting. The vehicle track noise, being very similar to that of the Bradley Fighting Vehicle (BFV), reported in Supplement 3, was not measured.


DTIC
ELECTE
APR 04 1986
S D



DTIC FILE COPY

Approved for public release; distribution unlimited.

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

| REPORT DOCUMENTATION PAGE | | READ INSTRUCTIONS BEFORE COMPLETING FORM |
|---|--------------------------------------|--|
| 1. REPORT NUMBER CERL TR N-60 | 2. GOVT ACCESSION NO. ADR 166 490 | 3. RECIPIENT'S CATALOG NUMBER |
| 4. TITLE (and Subtitle) ACOUSTIC DIRECTIVITY PATTERNS FOR ARMY WEAPONS SUPPLEMENT 4: THE MULTIPLE LAUNCH ROCKET SYSTEM | | 5. TYPE OF REPORT & PERIOD COVERED Final |
| | | 6. PERFORMING ORG. REPORT NUMBER |
| 7. AUTHOR(s) Paul D. Schomer | | 8. CONTRACT OR GRANT NUMBER(s) IAO-MLRS-85-01 |
| 9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Construction Engr Research Laboratory P.O. Box 4005 Champaign, IL 61820-1305 | | 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS |
| 11. CONTROLLING OFFICE NAME AND ADDRESS | | 12. REPORT DATE February 1986 |
| | | 13. NUMBER OF PAGES |
| 14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) | | 15. SECURITY CLASS. (of this report) unclassified |
| | | 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE |
| 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited. | | |
| 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) Copies are obtainable from the National Technical Information Service Springfield, VA 22161 | | |
| 18. SUPPLEMENTARY NOTES | | |
| 19. KEY WORDS (Continue on reverse side if necessary and identify by block number) noise (sound) acoustic directivity patterns Multiple Launch Rocket System MLRS | | |
| 20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Environmental noise emissions of the Multiple Launch Rocket System (MLRS) weapon were measured in order to develop acoustic directivity patterns. Ignition noise was analyzed using C-weighting and separated from rocket engine noise, which was analyzed using A-weighting. The vehicle track noise, being very similar to that of the Bradley Fighting Vehicle (BFV), reported in Supplement 3, was not measured. | | |

FOREWORD

This effort was funded by the U.S. Army Missile Command, Redstone Arsenal, AL under IAO MLRS-85-01, dated 26 November 1984, Change 1, dated 25 June 1985.

The work was done by the Environmental Division (EN), U.S. Army Construction Engineering Research Laboratory (USA-CERL). Dr. R. K. Jain is Chief of EN. Dr. L. R. Shaffer is Technical Director of USA-CERL, and COL Paul J. Theuer is Commander and Director.



| | |
|--------------------|--|
| Accession For | |
| NTIS CRA&I | <input checked="checked" type="checkbox"/> |
| DTIC TAB | <input type="checkbox"/> |
| Unannounced | <input type="checkbox"/> |
| Justification | |
| By | |
| Distribution / | |
| Availability Codes | |
| Dist | Avail and/or Special |
| A-1 | |

CONTENTS

| | Page |
|--|------|
| DD FORM 1473 | 1 |
| FOREWORD | 3 |
| LIST OF FIGURES AND TABLES | 5 |
| 1 INTRODUCTION | 7 |
| 2 DATA COLLECTION | 8 |
| 3 CONCLUSIONS | 11 |
| APPENDIX A: Measurement Site Coordinates | 12 |
| APPENDIX B: Comparison of Vehicle and Alternate C-4 Detonation Sites | 19 |
| APPENDIX C: Analysis of MLRS Ignition Data | 20 |
| DISTRIBUTION | |

TABLES

| Number | Page |
|--|------|
| 1 Firing Sequence at WSMR, January 1985 | 10 |
| 2 Analyzed Data in dB Listed by Event; SCEL of C-4 Blasts and Rocket Ignitions | 10 |
| 3 Input Data in dB for BNOISE 3.2 Position (Degrees) | 11 |
| 4 Measured Average ASEL for Rocket Motor | 11 |
| 5 Computer ASEL vs Distance by Site | 11 |
| B1 Inner Ring Sites, Comparison Between Vehicle and Alternate C-4 Sites for Placing Calibrations 5-lb Charge (CSEL) | 19 |
| B2 Outer Ring Sites, Comparison Between Vehicle and Alternate C-4 Sites for Placing Calibrations 5-lb Charge (CSEL) | 19 |
| C1 Average of Events by Grouping and Position | 20 |
| C2 Average of Consecutive Sets of C-4 | 20 |
| C3 Correction Table To Convert Measured Rocket Data to Omnidirectional Site; Independent Data re 5 lb of C-4 (119 dB at 250 m) | 20 |
| C4 Corrected Rocket Data by Group re 5 lb of C-4 (119 dB at 250 m) | 20 |
| C5 Rocket Data Corrected to Standard Measurement Positions re 5 lb of C-4 | 21 |
| C6 Rocket Data Averaged To Be Symmetrical re 5 lb of C-4 | 21 |
| C7 Input Data for BNOISE 3.2 Position (Degrees) | 21 |
| C8 CSEL Outer Ring Data; C-4 from Blue Box, Rocket-Ignition from Data 6000 | 21 |
| C9 Average of Events by Grouping and Position | 22 |
| C10 Differences in dB Between the Inner and Outer Rings by Radial Position | 22 |

FIGURES

| | |
|--|---|
| 1 General Site Layout for Noise Measurements of the MLRS at WSMR, January 1985 | 9 |
| 2 Microphone Layout, WSMR, January 1985 | 9 |

ACOUSTIC DIRECTIVITY PATTERNS FOR ARMY WEAPONS: SUPPLEMENT 4: THE MULTIPLE LAUNCH ROCKET SYSTEM

1 INTRODUCTION

Background

On 20 May 1981, the Army instituted the Installation Compatible Use Zone program (ICUZ). Under ICUZ, an Army installation works with the local civilian community to find ways to prevent or lessen the encroachment of off-installation housing and other noise-sensitive land uses into areas that are, or are likely to be, impacted by Army training noise.¹

Vital to the success of the ICUZ program is a noise-prediction computer tool developed by the U.S. Army Construction Engineering Research Laboratory (USA-CERL). The Integrated Noise Contour System (INCS) creates noise zone maps using data on the type, frequency, and time of training operations; weapons types and charge sizes; and target and firing point locations. These zone maps portray the yearly average total noise emissions of an installation. When overlayed on a map of an installation and its environs, these zones identify existing or potential conflicts between noise levels produced by training operations and noise-sensitive land uses on or near an installation. Using BNOISE 3.2, the blast noise prediction computer program associated with INCS, zone maps also can be created that predict how changes in training range operations, siting, use intensity, and weapon types will alter an installation's noise-impact profile.² The Army Environmental Hygiene Agency (AEHA) can make noise predictions for any Army installation using USA-CERL's INCS/BNOISE 3.2 program.

Zone maps predict total yearly average noise emissions of an installation. Whether a noise problem exists,

however, depends on numerous factors such as proximity of noise-sensitive land uses to range areas, weapon type, frequencies of operations, and time of day. For this reason, no "acceptable" or "excessive" levels have been defined for specific weapons. Nevertheless, one important data type needed for INCS/BNOISE 3.2 is the individual acoustic directivity pattern associated with each impulse-noise-producing weapon in the Army inventory. These patterns form a standard module of data for the INCS/BNOISE 3.2 prediction program.

USA-CERL Technical Report (TR) N-60 lists directivity pattern data obtained during tests at Fort Sill, OK, for many weapons used routinely in Army training.³ Supplements, 1, 2, and 3 to TR N-60 contain directivity pattern data for the LAW and TOW anti-tank weapons, three regularly used weapon simulators; the proposed Abrams Tank (M1-E1) 120-mm main gun; and the Bradley Fighting Vehicle 25-mm M242 main gun, respectively.

Purpose

The purpose of this study was to determine the acoustic directivity pattern of Multiple Launch Rocket System (MLRS) emissions. (The vehicle track and engine noises were not measured for this test since this vehicle is acoustically very similar to the Bradley Fighting Vehicle.)

Approach

Noise measurements were made on the MLRS at White Sands Missile Range, (WSMR), NM. The measurement method was basically the same as that described in USA-CERL TR N-60. Weapon firings were interspersed with detonations of C-4 plastic explosive. The C-4 was used to "calibrate" the site and provide for correcting the data for wind and terrain effects.

Mode of Technology Transfer

The directivity patterns obtained from this study have been added to the INCS/BNOISE 3.2 input data bank and are available for use by AEHA and all Department of Defense activities.

¹ Paul D. Schomer, "Noise Impact Prediction and Control," *Military Engineer*, Volume 74, Number 479 (April 1982).

² Paul D. Schomer, et al., *Blast Noise Prediction Volume I: Data Bases and Computational Procedures*, and Lincoln M. Little, et al., *Volume II: BNOISE 3.2 Computer Program Description and Program Listing*, Technical Report N-98/ADA 099440 and ADA099335 (U.S. Army Construction Engineering Research Laboratory [USA-CERL], 1981).

³ P. D. Schomer, L. M. Little, and A. B. Hunt, *Acoustic Directivity Patterns for Army Weapons*, Technical Report N-60/ADA066223 (USA-CERL, 1979).

2 DATA COLLECTION AND REDUCTION

Data Collection

Measurements were performed at WSMR as part of the Fly To Buy test at that facility. The test site was the Tula range for the MLRS at WSMR. Figure 1 shows the general test area, Figure 2 shows the detailed test site layout, and Appendix A contains measurement site coordinates. There were two concentric rings of sensors; the inner ring had a radius of 250 m and the outer ring had a radius of 500 m. Both sensor rings were on flat open areas. (The inner ring provides the primary data; the outer ring is used for quality control as outlined in TR N-60, Supplement 2, Appendix C.) Sensors were located 90° to the right of the line-of-fire (LOF) rather than at 120° because of the protective berm (Figure 2). The measurements were made during January 1985.

For this test, there were two C-4 firing points: one by the MLRS vehicle and one about 100 ft* to the left of the vehicle (Figure 2). Because C-4 could not be set close to the vehicle and test van, the site to the left was used for the actual test. Events 1 through 10 were used to compare C-4 at the vehicle point versus C-4 at the alternate site. These data, contained in Appendix B, show no significant differences in the results when the C-4 site was changed.

The microphones on the inner ring were Endevco piezoresistive transducers close-coupled to USA-CERL-built preamplifiers and line drivers. (Appendix B of Supplement 1 describes the Endevco device and the USA-CERL preamplifiers.) Each microphone was wired to the USA-CERL mobile field acoustics laboratory, where the signal was recorded on an Ampex PR2230 14-channel FM recorder.

The outer ring consisted of a variety of equipment. Sites 8 through 12 each had a B&K 4921 outdoor microphone, a USA-CERL "Blue-Box" noise monitor,⁴ and a Nagra DJ tape recorder. Sites 8 and 12 were operated over a long cable by personnel at sites 9 and 11, respectively. USA-CERL line drivers were used to vary amplifier gain for these two remote stations.

*1 ft = 0.3048 m.

⁴Aaron Averbuch, et al., *True-Integrating Environmental Noise Monitor and Sound-Exposure Level Meter, Volumes I through IV*, Technical Report N-41/ADA050958, ADA072002, ADA083320, and ADA083321 (USA-CERL, 1978, 1979, and 1980).

Site 7 had a B&K 4921 microphone system connected over a long line to the van and its PR2230 FM tape recorder. USA-CERL Blue-Box noise monitors were also used in the van for immediate data checking and readout.

Calibration

Calibration was performed (1) at the beginning and end of each tape and/or testing period, (2) when the equipment or equipment placement was changed, and (3) when any equipment malfunction was suspected. The six Endevco stations were calibrated with a B&K 4420 pistonphone. USA-CERL constructed special housings for the Endevco microphones so calibration could be performed using standard laboratory and field devices. At the beginning of each FM tape, the calibration tone was recorded for about 15 seconds at the measurement tape speed of 30 in./second (762 mm/second). The B&K 4921 microphone system was calibrated initially using the B&K-type 4220 pistonphone. Subsequent calibrations were performed using its internal 1000-Hz electrostatic actuator.

Test Sequence

The standard MLRS round was tested. Table 1 lists the test sequence for these rounds and the C-4 calibration shots. This is essentially the same procedure used during the original Fort Sill measurements and the measurements described in Supplements 1, 2, and 3.

Data Reduction

Initial data reduction was performed using the USA-CERL-developed True-Integrating Environmental Noise Monitor and Sound-Exposure Level Meter. This data reduction resulted in a measure of the C-weighted sound exposure level (CSEL). The Data 6000 computing oscilloscope was used to remeasure all inner ring sites in order to separate ignition (blast) noise from the more continuous motor noise. Background noise was also measured to ensure that the recorded data were far enough above the noise level to be valid. Table 2 lists analyzed ignition (blast) data by event.

The ignition data were first corrected by the adjacent (in-time) C-4 calibration events (11, 12, and 20 through 23). The C-4 data were corrected to data for an omnidirectional hemispherical (actually circular in the ground plane) radiating source. The MLRS data were averaged by microphone and corrected by the set of numbers found to convert the C-4 to a perfect, circular source. These averages are listed in Appendix C. These individual MLRS data (after correction by adjacent C-4 calibration) were then combined (energy-averaged by microphone) to form




Figure 1. General site layout for noise measurements of the MLRS at WSMR, January 1985.




Figure 2. Microphone layout, White Sands Missile Range, NM, January 1985.

Table 1
Firing Sequence at WSMR²,
January 1985

| Event(s) | Type |
|----------|---|
| #11, #12 | C-4 (1-1/4 lb) |
| #13 | Single MLRS |
| #14-#19 | 6 Ripple-Fired MLRS (4.5 Seconds Apart) |
| #20, #23 | C-4 (1-1/4 lb) |

*Events 1 through 10 were used as part of the C-4 site test.
The data are in Appendix B.

Table 2
Analyzed Data in dB Listed by Event
CSEL of C-4 Blasts and Rocket Ignitions

| Event | 1 | 2 | 3 | 4 | 5 | 6 |
|--------------------|-------|-------|-------|-------|-------|-------|
| 11-C4 | 124.8 | 120.4 | 121.0 | 119.9 | 123.3 | 125.6 |
| 12-C4 | 123.5 | 118.6 | 119.5 | 119.0 | 123.3 | 125.3 |
| 13-Rocket Ignition | 111.1 | 111.3 | 112.8 | 116.5 | 115.4 | 112.1 |
| 14-Rocket Ignition | 110.9 | 111.2 | 114.0 | 118.2 | 115.4 | 113.9 |
| 15-Rocket Ignition | 110.8 | 109.0 | 112.9 | 115.3 | 113.0 | 110.1 |
| 16-Rocket Ignition | 110.1 | 109.3 | 112.0 | 111.3 | 115.8 | 108.5 |
| 17-Rocket Ignition | 111.8 | 110.1 | 113.1 | 112.3 | 116.1 | 109.7 |
| 18-Rocket Ignition | 110.5 | 109.9 | 112.0 | 115.3 | 115.7 | 109.6 |
| 19-Rocket Ignition | 109.6 | 110.5 | 113.2 | 112.8 | 115.5 | 111.2 |
| 20-C4 | 122.4 | 119.8 | 120.0 | 119.0 | 122.1 | 122.0 |
| 21-C4 | 122.2 | 118.4 | 119.5 | 118.3 | 121.4 | 123.7 |
| 22-C4 | 122.3 | 119.4 | 119.7 | 118.9 | 121.4 | 122.9 |
| 23-C4 | 122.8 | 119.3 | 119.7 | 118.6 | 121.0 | 122.3 |

the overall weapon-device directivity pattern. Corrections were made to form a symmetrical pattern. Appendix D lists the resultant data by weapon/device.

Table 3, which is based on the data given in Appendix D, lists the data as they are included in the BNOISE 3.2 weapons input table. In the table, the reference distance is 250 m. At this distance, 1-1/4 lb (0.57 kg) of C-4 exploded on the ground typically produces a CSEL of 115 dB.

Rocket Motor Noise Measurements

Currently, AEHA can include motor noise assessments as part of a general noise assessment as required on a case-by-case basis; the computerized INCS does

not include a module for this. In the future a module in INCS may include this type of noise or it can be modeled as for a helicopter. With this case-by-case application of AEHA and the possible future INCS module in mind, rocket motor noise emission data were gathered for the MLRS. These data can be used by AEHA or as part of a new noise assessment module in INCS, if one is developed.

Table 4 lists the measured A-weighted SEL (ASEL) at the inner ring sites. Maximum 1/2 second, 1/3-octave data were developed, and in a similar fashion to helicopters, ASEL versus distance curves were developed. These are listed in Table 5 for the directions (with respect to LOF) indicated.

Table 3
Input Data in dB for BNOISE 3.2 Position (Degrees)

| | 0 | 30 | 60 | 90 | 120 | 150 | 180 | 210 | 240 | 270 | 300 | 330 | Ave |
|-----------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Value | 106.3 | 107.4 | 108.2 | 111.0 | 112.7 | 114.0 | 115.0 | 114.0 | 112.7 | 111.0 | 108.2 | 107.4 | 111.6 |
| Value re rear of MLRS | -8.7 | -7.6 | -6.8 | -4.0 | -2.3 | -1.0 | 0 | -1.0 | -2.3 | -4.0 | -6.8 | -7.6 | -5.3 |

Table 4
Measured Average ASEL in dB for Rocket Motor

| Site | ASEL |
|------|-------|
| 1 | 120.4 |
| 2 | 115.6 |
| 3 | 114.4 |
| 4 | 98.9 |
| 5 | 109.9 |
| 6 | 114.7 |

Table 5
Computer ASEL vs Distance by Site, dB

| Distance (m) | Site 1 | Site 2 | Site 3 | Site 4 | Site 5 | Site 6 |
|--------------|--------|--------|--------|--------|--------|--------|
| 50 | 127.0 | 123.1 | 121.7 | 106.0 | 116.0 | 121.9 |
| 100 | 124.0 | 120.1 | 118.7 | 103.0 | 113.0 | 118.8 |
| 200 | 121.0 | 117.1 | 115.6 | 99.9 | 110.0 | 115.8 |
| 500 | 117.0 | 113.1 | 111.7 | 96.0 | 106.0 | 111.9 |
| 1000 | 114.0 | 110.1 | 108.7 | 93.0 | 103.0 | 108.8 |
| 2000 | 111.0 | 107.1 | 105.6 | 89.9 | 100.0 | 105.8 |
| 5000 | 107.0 | 103.1 | 101.7 | 86.0 | 96.0 | 101.9 |
| 10000 | 104.0 | 100.1 | 98.7 | 83.0 | 93.0 | 98.8 |

3 CONCLUSIONS

This report gives the acoustic directivity patterns for the ignition noise of the MLRS M270 Armored Vehicle Mounted Rocket Launcher. These data supplement the pattern data presented in USA-CERL

Technical Report N-60. These supplemental pattern data have been included in the weapon directivity pattern load module of BNOISE 3.2 and made available to users of the Integrated Noise Contour System. The motor noise emissions were also gathered for future use.

APPENDIX A: MEASUREMENT SITE COORDINATES

This appendix contains three documents from WSMR.

1. Coordinates and diagram of the earthen berm.
2. Coordinates of the preliminary measurement sites and the locations of three USA-CERL personnel (P1, P2, and P3).
3. Locations of final adjusted measurement sites #3, #7, and #9 and the alternate C-4 site, #D.

Notes:

1. Measurement site numbers correspond with those shown in Figure 2.
2. For WSTM coordinates, X is east-west, Y is north-south, H is altitude above mean sea level.
3. The firing point WSTM coordinates are:

X = 545,832 ft
Y = 431,405 ft
H = 4,130 ft



DEFENSE MAPPING AGENCY

HYDROGRAPHIC/TOPOGRAPHIC CENTER
GEODETIC SURVEY SQUADRON
DETACHMENT 2
WHITE SANDS MISSILE RANGE
NEW MEXICO 88002

sl
Mr. St. Leon/sy/3718
25 February 1985

SURVEY #56-85

WSD-73 (NAD)

MLRS BERM POINTS

AT TULA-G

Surveyed 14 February 1985. Filed in MLRS Folder.

| <u>GEODETIC COORDINATES</u> | <u>WSTM COORDINATES*</u> | <u>WSCS COORDINATES</u> | <u>UTM COORDINATES</u> |
|-----------------------------|--------------------------|-------------------------|------------------------|
| BERM POINT #1 | | | |
| ϕ = 33° 04' 40.8808" | X = 546,084.94 ft | E = 546,095.04 ft | E = 389,590.81 m |
| λ = 106 10 58.4145 | Y = 431,599.34 | N = 498,100.27 | N = 3,660,367.26 |
| $\Delta\alpha$ = 00 04 56 | H = 4,104.07 | Z = 4,053.28 | H = 1,250.92 |
| BERM POINT #2 | | | |
| ϕ = 33 04 40.6485 | X = 546,187.22 | E = 546,197.35 | E = 389,621.89 |
| λ = 106 10 57.2129 | Y = 431,576.01 | N = 498,076.94 | N = 3,660,359.76 |
| $\Delta\alpha$ = 00 04 56 | H = 4,104.95 | Z = 4,053.93 | H = 1,251.19 |
| BERM POINT #3 | | | |
| ϕ = 33 04 37.2488 | X = 546,149.09 | E = 546,159.21 | E = 389,608.94 |
| λ = 106 10 57.6668 | Y = 431,232.35 | N = 497,733.20 | N = 3,660,255.19 |
| $\Delta\alpha$ = 00 04 56 | H = 4,104.24 | Z = 4,053.27 | H = 1,250.98 |
| BERM POINT #4 | | | |
| ϕ = 33 04 37.4143 | X = 546,054.89 | E = 546,064.99 | E = 389,580.30 |
| λ = 106 10 58.7735 | Y = 431,248.95 | N = 497,749.80 | N = 3,660,260.61 |
| $\Delta\alpha$ = 00 04 55 | H = 4,104.34 | Z = 4,053.58 | H = 1,251.01 |
| BERM POINT #5 | | | |
| ϕ = 33 04 39.6399 | X = 546,116.01 | E = 546,126.17 | E = 389,599.80 |
| λ = 106 10 58.0514 | Y = 431,473.96 | N = 497,974.87 | N = 3,660,328.94 |
| $\Delta\alpha$ = 00 04 56 | H = 4,124.43 | Z = 4,073.55 | H = 1,257.13 |
| BERM POINT #6 | | | |
| ϕ = 33 04 39.5763 | X = 546,144.82 | E = 546,154.98 | E = 389,608.55 |
| λ = 106 10 57.7130 | Y = 431,467.58 | N = 497,968.48 | N = 3,660,326.88 |
| $\Delta\alpha$ = 00 04 56 | H = 4,123.63 | Z = 4,072.69 | H = 1,256.88 |

SURVEY #56-85 MLRS BERM POINTS AT TULA-G
25 February 1985

| <u>GEODETIC COORDINATES</u> | <u>WSTM COORDINATES</u> | <u>WCS COORDINATES</u> | <u>UTM COORDINATES</u> |
|-----------------------------------|-----------------------------|-----------------------------|----------------------------|
| BERM POINT #7 | | | |
| $\phi = 33^{\circ} 04' 38.6923''$ | $X = 546,129.98 \text{ ft}$ | $E = 546,140.15 \text{ ft}$ | $E = 389,603.68 \text{ m}$ |
| $\lambda = 106 10 57.8889$ | $Y = 431,378.22$ | $N = 497,879.10$ | $N = 3,660,299.71$ |
| $\Delta\alpha = 00 04 56$ | $H = 4,125.56$ | $Z = 4,074.64$ | $H = 1,257.47$ |


| | | | |
|----------------------------|------------------|------------------|--------------------|
| BERM POINT #8 | | | |
| $\phi = 33 04 38.7356$ | $X = 546,104.15$ | $E = 546,114.30$ | $E = 389,595.82$ |
| $\lambda = 106 10 58.1924$ | $Y = 431,382.55$ | $N = 497,883.43$ | $N = 3,660,301.13$ |
| $\Delta\alpha = 00 04 56$ | $H = 4,125.31$ | $Z = 4,074.45$ | $H = 1,257.40$ |

TRUE AZIMUTH (from North) BERM POINT #4 TO BERM POINT #1 = $04^{\circ} 59' 00''$

Terry D. Beckett
TERRY D. BECKETT
Chief, Detachment 2

TS 1018

WSTM COORDINATES
 $X = 546,121.73 \text{ ft}$
 $Y = 431,416.34$
 $H = 4,125.92$





DEFENSE MAPPING AGENCY

HYDROGRAPHIC/TOPOGRAPHIC CENTER

GEODETIC SURVEY SQUADRON

DETACHMENT 2

WHITE SANDS MISSILE RANGE

NEW MEXICO 88002

sl
Mr. St. Leon/sy/3718
27 November 1984

SURVEY #494-84

WSD-73 (NAD)

MLRS NOISE POINTS

Surveyed 8 November 1984. Filed in MLRS Folder.

| <u>GEODETIC COORDINATES</u> | <u>WSTM COORDINATES</u> | <u>WSCS COORDINATES</u> | <u>UTM COORDINATES</u> |
|-----------------------------|-------------------------|-------------------------|------------------------|
| MLRS NOISE 1 | | | |
| ϕ = 33° 04' 44.7010" | X = 545,252.01 ft | E = 545,261.92 ft | E = 389,338.50 m |
| λ = 106 11 08.1966 | Y = 431,984.25 | N = 498,485.27 | N = 3,660,487.77 |
| $\Delta\alpha$ = +00 04 50 | H = 4,095.25 | Z = 4,046.30 | H = 1,248.23 |
| MLRS NOISE 2 | | | |
| ϕ = 33 04 46.7910 | X = 546,043.91 | E = 546,053.99 | E = 389,580.62 |
| λ = 106 10 58.8866 | Y = 432,196.62 | N = 498,697.68 | N = 3,660,549.41 |
| $\Delta\alpha$ = +00 04 55 | H = 4,097.67 | Z = 4,047.01 | H = 1,248.97 |
| MLRS NOISE 3 | | | |
| ϕ = 33 04 36.8472 | X = 546,623.13 | E = 546,633.35 | E = 389,753.23 |
| λ = 106 10 52.0967 | Y = 431,192.45 | N = 497,693.29 | N = 3,660,241.20 |
| $\Delta\alpha$ = +00 04 59 | H = 4,106.26 | Z = 4,054.24 | H = 1,251.59 |
| MLRS NOISE 4 | | | |
| ϕ = 33 04 33.2115 | X = 546,411.46 | E = 546,421.65 | E = 389,687.31 |
| λ = 106 10 54.5904 | Y = 430,824.69 | N = 497,325.45 | N = 3,660,129.96 |
| $\Delta\alpha$ = +00 04 58 | H = 4,106.42 | Z = 4,054.82 | H = 1,251.64 |
| MLRS NOISE 5 | | | |
| ϕ = 33 04 31.1214 | X = 545,619.27 | E = 545,629.28 | E = 389,445.10 |
| λ = 106 11 03.9034 | Y = 430,612.32 | N = 497,113.03 | N = 3,660,068.31 |
| $\Delta\alpha$ = +00 04 53 | H = 4,102.73 | Z = 4,052.84 | H = 1,250.51 |
| MLRS NOISE 6 | | | |
| ϕ = 33 04 36.8684 | X = 545,039.41 | E = 545,049.29 | E = 389,270.66 |
| λ = 106 11 10.7080 | Y = 431,192.34 | N = 497,693.18 | N = 3,660,247.29 |
| $\Delta\alpha$ = +00 04 49 | H = 4,099.83 | Z = 4,051.27 | H = 1,249.63 |
| MLRS NOISE 7 | | | |
| ϕ = 33 04 50.4462 | X = 544,672.00 | E = 544,681.80 | E = 389,164.01 |
| λ = 106 11 15.0034 | Y = 432,564.11 | N = 499,065.25 | N = 3,660,666.70 |
| $\Delta\alpha$ = +00 04 47 | H = 4,104.37 | Z = 4,056.71 | H = 1,251.02 |

SURVEY #494-84 MLRS NOISE POINTS
27 November 1984

| <u>GEODETIC COORDINATES</u> | <u>WSTM COORDINATES</u> | <u>WSCS COORDINATES</u> | <u>UTM COORDINATES</u> |
|-----------------------------|-------------------------|-------------------------|------------------------|
| MLRS NOISE 8 | | | |
| ϕ = 33° 04' 54.6221" | X = 546,256.07 ft | E = 546,266.19 ft | E = 389,648.33 m |
| λ = 106 10 56.3799 | Y = 432,988.39 | N = 499,489.63 | N = 3,660,789.85 |
| $\Delta\alpha$ = +00 04 57 | H = 4,091.07 | Z = 4,039.98 | H = 1,246.96 |
| MLRS NOISE 9 | | | |
| ϕ = 33 04 34.7348 | X = 547,415.35 | E = 547,425.76 | E = 389,993.80 |
| λ = 106 10 42.7904 | Y = 430,980.11 | N = 497,480.91 | N = 3,660,173.43 |
| $\Delta\alpha$ = +00 05 04 | H = 4,110.09 | Z = 4,056.26 | H = 1,252.76 |
| MLRS NOISE 10 | | | |
| ϕ = 33 04 27.4646 | X = 546,991.48 | E = 547,001.79 | E = 389,861.80 |
| λ = 106 10 47.7842 | Y = 430,244.70 | N = 496,745.34 | N = 3,659,950.99 |
| $\Delta\alpha$ = +00 05 01 | H = 4,107.17 | Z = 4,054.19 | H = 1,251.87 |
| MLRS NOISE 11 | | | |
| ϕ = 33 04 23.2888 | X = 545,407.12 | E = 545,417.08 | E = 389,377.39 |
| λ = 106 11 06.4097 | Y = 429,820.39 | N = 496,320.93 | N = 3,659,827.83 |
| $\Delta\alpha$ = +00 04 51 | H = 4,107.06 | Z = 4,057.51 | H = 1,251.84 |
| MLRS NOISE 12 | | | |
| ϕ = 33 04 34.7803 | X = 544,247.68 | E = 544,257.43 | E = 389,028.59 |
| λ = 106 11 20.0157 | Y = 430,980.19 | N = 497,480.98 | N = 3,660,185.71 |
| $\Delta\alpha$ = +00 04 44 | H = 4,122.97 | Z = 4,076.07 | H = 1,256.68 |
| MLRS NOISE P1 | | | |
| ϕ = 33 04 28.6437 | X = 544,787.66 | E = 544,797.49 | E = 389,190.73 |
| λ = 106 11 13.6802 | Y = 430,360.73 | N = 496,861.39 | N = 3,659,994.87 |
| $\Delta\alpha$ = +00 04 47 | H = 4,106.14 | Z = 4,058.01 | H = 1,251.55 |
| MLRS NOISE P2 | | | |
| ϕ = 33 04 49.2686 | X = 546,875.32 | E = 546,885.60 | E = 389,834.93 |
| λ = 106 10 49.1114 | Y = 432,448.22 | N = 498,949.34 | N = 3,660,622.86 |
| $\Delta\alpha$ = +00 05 01 | H = 4,102.37 | Z = 4,049.88 | H = 1,250.40 |
| MLRS NOISE P3 | | | |
| ϕ = 33 04 35.1572 | X = 547,256.94 | E = 547,267.32 | E = 389,945.70 |
| λ = 106 10 44.6512 | Y = 431,022.57 | N = 497,523.38 | N = 3,660,186.98 |
| $\Delta\alpha$ = +00 05 03 | H = 4,110.12 | Z = 4,056.66 | H = 1,252.77 |

SURVEY #494-84 MLRS NOISE POINTS
27 November 1984

| <u>POINT TO POINT</u> | | <u>WSM AZIMUTH)</u> (from North) |
|-------------------------|--|-------------------------------------|
| L-597 B to MLRS NOISE 1 | | 315° 00' 18" |
| " " MLRS NOISE 2 | | 15 00 02 |
| " " MLRS NOISE 3 | | 104 59 55 |
| " " MLRS NOISE 4 | | 135 00 01 |
| " " MLRS NOISE 5 | | 195 00 28 |
| " " MLRS NOISE 6 | | 255 00 28 |
| " " MLRS NOISE 7 | | 314 59 55 |
| " " MLRS NOISE 8 | | 15 00 02 |
| " " MLRS NOISE 9 | | 105 00 05 |
| " " MLRS NOISE 10 | | 134 59 58 |
| " " MLRS NOISE 11 | | 195 00 09 |
| " " MLRS NOISE 12 | | 255 00 14 |
| " " MLRS NOISE P1 | | 225 00 22 |
| " " MLRS NOISE P2 | | 44 59 56 |
| " " MLRS NOISE P3 | | 105 00 03 |


TERRY D. BECKETT
Chief, Detachment 2



DEFENSE MAPPING AGENCY

HYDROGRAPHIC/TOPOGRAPHIC CENTER
GEODETIC SURVEY SQUADRON
DETACHMENT 2
WHITE SANDS MISSILE RANGE
NEW MEXICO 88002

sl
Mr. St. Leon/sy/3718
19 December 1984

SURVEY #558-84

WSD-73 (NAD)

MLRS NOISE POINTS

Surveyed 13 December 1984. Filed in MLRS Folder.

| <u>GEODETIC COORDINATES</u> | <u>WSTM COORDINATES</u> | <u>WSCS COORDINATES</u> | <u>UTM COORDINATES</u> |
|-----------------------------------|-----------------------------|-----------------------------|----------------------------|
| MLRS NOISE 3A | | | |
| $\phi = 33^{\circ} 04' 44.6854''$ | $X = 546,411.43 \text{ ft}$ | $E = 546,421.61 \text{ ft}$ | $E = 389,691.79 \text{ m}$ |
| $\lambda = 106 10 54.5711$ | $Y = 431,984.33$ | $N = 498,485.35$ | $N = 3,660,483.31$ |
| $\Delta\alpha = +00 04 58$ | $H = 4,103.6\text{t}$ | $Z = 4,052.1\text{t}$ | $H = 1,250.8\text{t}$ |
| MLRS NOISE 7A | | | |
| $\phi = 33 04 49.3615$ | $X = 544,781.39$ | $E = 544,791.21$ | $E = 389,196.92$ |
| $\lambda = 106 11 13.7196$ | $Y = 432,454.62$ | $N = 498,955.74$ | $N = 3,660,632.92$ |
| $\Delta\alpha = +00 04 47$ | $H = 4,102.6\text{t}$ | $Z = 4,054.7\text{t}$ | $H = 1,250.5\text{t}$ |
| MLRS NOISE 9A | | | |
| $\phi = 33 04 51.0092$ | $X = 547,051.14$ | $E = 547,061.46$ | $E = 389,889.19$ |
| $\lambda = 106 10 47.0422$ | $Y = 432,624.40$ | $N = 499,125.56$ | $N = 3,660,675.86$ |
| $\Delta\alpha = +00 05 02$ | $H = 4,108.3\text{t}$ | $Z = 4,055.4\text{t}$ | $H = 1,252.2\text{t}$ |
| MLRS NOISE D | | | |
| $\phi = 33 04 38.2579$ | $X = 545,761.04$ | $E = 545,771.07$ | $E = 389,491.09$ |
| $\lambda = 106 11 02.2254$ | $Y = 431,333.78$ | $N = 497,834.65$ | $N = 3,660,287.60$ |
| $\Delta\alpha = +00 04 54$ | $H = 4,101.8\text{t}$ | $Z = 4,051.7\text{t}$ | $H = 1,250.2\text{t}$ |

Terry D. Beckett

TERRY D. BECKETT
Chief, Detachment 2

APPENDIX B:
COMPARISON OF VEHICLE AND ALTERNATE C-4 DENOTATION SITES (Figure 2)

As shown in Tables B1 and B2, the differences are random, usually less than 1 dB, and inconsequential.

Table B1
Inner Ring Sites, Comparison Between Vehicle and Alternate C-4 Sites
for Placing Calibrations 5-lb Charge (CSEL)

| Site No. | | 1 | 2 | 3 | 4 | 5 | 6 |
|---|------------------|-------|-------|-------|-------|-------|-------|
| MLRS Vehicle Site (Victor) | Event No. | | | | | | |
| | 2 | 112.0 | 113.2 | 111.9 | 106.5 | 111.0 | 109.8 |
| | 4 | 112.6 | 112.1 | 113.6 | 109.4 | 109.6 | 107.2 |
| | 6 | 111.6 | 111.1 | 111.8 | 108.4 | 110.4 | 111.0 |
| | 8 | 112.1 | 111.2 | 112.2 | 108.1 | 108.4 | 109.5 |
| | 9 | 112.3 | 111.1 | 112.9 | 108.1 | 108.8 | 108.9 |
| | 10 | 112.0 | 111.6 | 112.1 | 107.1 | 109.2 | 107.6 |
| | Average | 112.1 | 111.7 | 112.4 | 107.9 | 109.6 | 109.0 |
| Alternate C-4 Site | 1 | 111.6 | 111.3 | 120.9 | 108.5 | 110.8 | 109.6 |
| | 3 | 113.4 | 111.3 | 111.5 | 108.4 | 111.0 | 109.9 |
| | 5 | 112.7 | 111.9 | 110.4 | 108.5 | 109.5 | 108.8 |
| | 7 | 113.5 | 111.2 | 111.4 | 109.1 | 111.0 | 110.0 |
| | Average | 112.8 | 111.4 | 113.6 | 108.6 | 110.6 | 109.6 |
| Difference, Vehicle Site Minus Alternate | | -0.7 | +0.3 | -1.2 | -0.7 | -1.0 | -0.6 |

Table B2
Outer Ring Sites, Comparison Between Vehicle and Alternate C-4 Sites
for Placing Calibrations 5-lb Charge (CSEL)

| Site No. | | 1 | 2 | 3 | 4 | 5 | 6 |
|---|------------------|--------|--------|------|------|------|------|
| MLRS Vehicle Site | Event No. | | | | | | |
| | 2 | 77.5 | 78.6 | 76.6 | 72.4 | 75.7 | 75.4 |
| | 4 | 77.7 | 78.0 | 78.6 | 73.8 | 74.4 | 72.5 |
| | 6 | 76.5 | 76.2 | 77.9 | 74.3 | 73.1 | 73.8 |
| | 8 | 76.9 | 76.7 | 78.4 | 73.4 | 71.2 | 75.6 |
| | 9 | 76.1 | 77.7 | 78.9 | 74.4 | 71.8 | 72.7 |
| | 10 | 75.8 | 77.2 | 77.3 | 73.3 | 72.8 | 73.6 |
| | Average | 76.8 | 77.4 | 78.0 | 73.6 | 73.2 | 74.0 |
| Alternate C-4 Site | 1 | 76.6 | 76.5 | 76.2 | 74.9 | 74.5 | 74.9 |
| | 3 | 78.3 | 76.7 | 76.7 | 74.6 | 74.5 | 75.2 |
| | 5 | 76.3 | 77.8 | 76.4 | 73.9 | 74.5 | 71.3 |
| | 7 | 77.9 | 76.5 | 76.9 | 74.2 | 74.4 | 74.1 |
| | Average | 77.3 | 76.9 | 76.6 | 74.4 | 74.5 | 73.9 |
| Difference, Vehicle Site Minus Alternate | | -0.475 | +0.525 | +1.4 | -0.8 | -1.3 | +0.1 |

**APPENDIX C:
ANALYSIS* OF MLRS IGNITION DATA**

Table C1
Average of Events by Grouping and Position

| Events | 1 | 2 | 3 | 4 | 5 | 6 | Group |
|--------|-------|-------|-------|-------|-------|-------|-------|
| 11,12 | 124.2 | 119.6 | 120.3 | 119.5 | 123.3 | 125.5 | C1 |
| 13-19 | 110.7 | 110.3 | 112.9 | 115.1 | 115.4 | 111.1 | R1 |
| 20-23 | 122.4 | 119.3 | 119.7 | 118.7 | 121.5 | 122.8 | C2 |

Table C2
Average of Consecutive Sets of C-4

| | 1 | 2 | 3 | 4 | 5 | 6 | Average |
|-----|-------|-------|-------|-------|-------|-------|---------|
| C12 | 123.4 | 119.5 | 120.0 | 119.1 | 122.5 | 124.4 | 122.0 |

Table C3
**Correction Table To Convert Measured Rocket Data to Omnidirectional Site
Independent Data re 5 lb of C-4 (119 dB at 250 m)**

| | 1 | 2 | 3 | 4 | 5 | 6 |
|------|-----|-----|-----|-----|-----|-----|
| CR12 | 4.4 | 0.5 | 1.0 | 0.1 | 3.5 | 5.4 |

Table C4
**Corrected Rocket Data by Group
re 5 lb of C-4 (119 dB at 250 m)**

| | 1 | 2 | 3 | 4 | 5 | 6 |
|----|-------|-------|-------|-------|-------|-------|
| R1 | 106.3 | 109.8 | 111.9 | 115.0 | 111.9 | 105.7 |

*As described in USA-CERL TR-N-60 Supplement 2, Appendix C.

Table C5
Rocket Data Corrected to Standard
Measurement Positions re 5 lb of C-4

| | 1 | 2 | 3 | 4 | 5 | 6 |
|----|-------|-------|-------|-------|-------|-------|
| R1 | 106.3 | 109.8 | 113.4 | 115.0 | 111.9 | 105.7 |

*Value altered from the 90° measurement position to the 120° standard position.

Table C6
Rocket Data Averaged To Be Symmetrical re 5 lb of C-4

| | 1 | 2 | 3 | 4 | 5 | 6 |
|----|-------|-------|-------|-------|-------|-------|
| R1 | 106.3 | 108.2 | 112.7 | 115.0 | 112.7 | 108.2 |

Table C7
Input Data for BNOISE 3.2 Position (Degrees)

| | 0 | 30 | 60 | 90 | 120 | 150 | 180 | 210 | 240 | 270 | 300 | 330 | Ave |
|-------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Value | 106.3 | 107.4 | 108.2 | 111.0 | 112.7 | 114.0 | 115.0 | 114.0 | 112.7 | 111.0 | 108.2 | 107.4 | 111.6 |
| Value r3 rear of gun | -8.7 | -7.6 | -6.8 | -4.0 | -2.3 | -1.0 | 0 | -1.0 | -2.3 | -4.0 | -6.8 | -7.6 | -5.3 |

Table C8
CSEL Outer Ring Data
C-4 From Blue Box, Rocket-Ignition From Data 6000

| Event | C4 from data 6000 | | | | | | | |
|-----------|-------------------|-------|-------|-------|-------|-------|-------|-------|
| | 7 | 8 | 9 | 10 | 11 | 12 | 11 | 12 |
| 11-C4 | 118.5 | 114.2 | 114.9 | 113.7 | - | - | 118.4 | 121.2 |
| 12-C4 | 117.4 | 111.7 | 112.4 | 112.3 | 120.6 | 121.5 | 117.3 | 119.4 |
| 13-Rocket | 107.1 | 103.6 | 101.6 | 108.4 | 113.2 | 107.9 | 113.2 | 107.9 |
| 14-Rocket | 107.6 | 104.2 | 102.8 | 109.5 | 113.4 | 109.6 | 113.4 | 109.6 |
| 20-C4 | 115.4 | 111.7 | 111.6 | 111.7 | 117.4 | 115.8 | 115.5 | 115.9 |
| 21-C4 | 114.2 | 110.5 | 111.1 | 110.7 | 116.7 | 117.8 | 114.9 | 117.9 |
| 22-C4 | 114.5 | 111.2 | 111.6 | 111.6 | 116.5 | 117.2 | 114.8 | 117.2 |
| 23-C4 | 114.7 | 111.9 | 112.5 | 111.3 | 116.4 | 116.4 | 114.7 | 116.6 |

Table C9
Average of Events by Grouping and Position

| | 7 | 8 | 9 | 10 | 11 | 12 | 11 | 12 |
|----|-------|-------|-------|-------|-------|-------|-------|-------|
| C1 | 118.0 | 113.1 | 113.8 | 113.1 | 120.6 | 121.5 | 117.9 | 120.4 |
| R1 | 107.4 | 103.9 | 102.2 | 109.0 | 113.3 | 108.8 | 113.3 | 108.8 |
| C2 | 114.7 | 111.4 | 111.7 | 111.3 | 116.8 | 116.9 | 115.0 | 117.0 |

Table C10 (Tables C1-C9)
Differences in dB Between the Inner and Outer Rings by Radial Position

| | 1-7 | 2-8 | 3-9 | 4-10 | 5-11 | 6-12 | 5-11 | 6-12 |
|----|-----|-----|------|------|------|------|------|------|
| C1 | 6.2 | 6.5 | 6.5 | 6.4 | 2.7 | 4.0 | 5.4 | 5.1 |
| R1 | 3.3 | 6.4 | 10.7 | 6.1 | 2.1 | 2.3 | 2.1 | 2.3 |
| C2 | 7.7 | 7.9 | 8.0 | 7.4 | 4.7 | 5.9 | 6.5 | 5.8 |

USA-CERL DISTRIBUTION

Defense Nuclear Agency
ATTN: DMA/FCCFF

Chief of Engineers
ATTN: DAEN-ASI-L (2)
ATTN: DAEN-CCP
ATTN: DAEN-CW
ATTN: DAEN-CWE
ATTN: DAEN-CWM-R
ATTN: DAEN-CWO
ATTN: DAEN-CWP
ATTN: DAEN-EC
ATTN: DAEN-ECC
ATTN: DAEN-ECE
ATTN: DAEN-ECR
ATTN: DAEN-ED
ATTN: DAEN-EDC
ATTN: DAEN-EDM
ATTN: DAEN-EM
ATTN: DAEN-ECE
ATTN: DAEN-ECP
ATTN: DAEN-ECI
ATTN: DAEN-ECH
ATTN: DAEN-ECH

FESA, ATTN: Library 22060
ATTN: DET III 79906

US Army Engineer Districts
ATTN: Library (41)

US Army Engineer Divisions
ATTN: Library (14)

US Army Europe
AEAN-ODCS/Engr 09403
ISAE 09081
V Corps
ATTN: DEN (11)
VII Corps
ATTN: DEN (15)
21st Support Command
ATTN: DEN (12)
USA Berlin
ATTN: DEN (11)
USASSETAF
ATTN: DEN (10)
Allied Command Europe (ACE)
ATTN: DEN (3)

8th USA, Korea (19)

ROK/US Combined Forces Command 96301
ATTN: EUSA-HHC-CFC/Engr

USA Japan (USARJ)
ATTN: AJEN-DEN 96343
ATTN: DEN-Honshu 96343
ATTN: DEN-Okinawa 96331

416th Engineer Command 60623
ATTN: Facilities Engineer

US Military Academy 10966
ATTN: Facilities Engineer
ATTN: Dept of Geography &
Computer Science
ATTN: DSCPER/MAEN-A

AMHRC, ATTN: DRXMR-ME 02172

USA ARRCOM 61299
ATTN: DRCS-RI-I
ATTN: DRCS-IS

AMC - Dir., Inst., & Servo
ATTN: DEN (23)

DLA ATTN: DLA-WI 22314

DNA ATTN: NADS 20305

FORSCOM
FORSCOM Engr, ATTN: APEN-DEN
ATTN: DEN (23)

RSC
ATTN: HSLO-P 78234
ATTN: Facilities Engineer
Pittsmons AMC 80240
Walter Reed AMC 20012

Dept. of the Army
ATTN: DAMO-RD
ATTN: DALO-SM

Deputy Chief of Staff
for Intelligence
ATTN: ACSI/DA

INSCOM - Ch, Instl. Div
ATTN: Facilities Engineer (3)

MDW, ATTN: DEN (3)

MTMC
ATTN: MTMC-SA 20315
ATTN: Facilities Engineer (3)

NARADCOM, ATTN: DRDNA-F 01760

TARCOM, Fac. Div. 48090

TRADOC
HQ, TRADOC, ATTN: ATEN-DEN
ATTN: DEN (19)

TSARCOM, ATTN: STSAS-F 63120

USACC, ATTN: Facilities Engr (2)

WESTCOM
ATTN: DEN, Ft. Shafter 96858
ATTN: APEN-IM

SHAPE 09055
ATTN: Surv. Section, CCB-OPS
Infrastructure Branch, LANDA

HQ USEUCOM 09128
ATTN: ECJ 4/7-LOE

FORT BELVOIR, VA 22060 (7)
ATTN: Canadian Liaison Office
ATTN: Water Resources Support Ctr
ATTN: Engr Studies Center
ATTN: Engr Topographic Lab.
ATTN: ATZA-DTE-SU
ATTN: ATZA-DTE-EM
ATTN: RAD Command

CRREL, ATTN: Library 03755

WES, ATTN: Library 39180

HQ, XVIII Airborne Corps
and Fort Bragg
ATTN: AFZA-FE-EE 28307

Area Engineer, AEDC-Area Office.
Arnold Air Force Station, TN 37389

Chanute AFB, IL 61868
3345 CES/DE, Stop 27

Norton AFB, CA 92409
ATTN: AFRC-MX/DEE

AFESC, Tyndall AFB, FL 32403

NAVFAC
ATTN: Engineering Command (7)
ATTN: Division Offices (6)
ATTN: Naval Public Works Center (9)
ATTN: Naval Civil Engr Lab. (3)

ATTN: Library, Code L08A NCEL 93043

Defense Technical Info. Center 22314
ATTN: DDA (2)

Engr Societies Library, NY 10017

Natl Guard Bureau Instl. Div 20310

US Govt Print Office 22304
Receiving Sect/Depository Copies (2)

US Army Env. Hygiene Agency
ATTN: HSRB-E 21010

National Bureau of Standards 20899

ENA Team Distribution

Chief of Engineers
ATTN: DAEN-ECE-E
ATTN: DAEN-ECE-B
ATTN: DAEN-ECE-I (2)
ATTN: DAEN-ZCF-B
ATTN: DAEN-ECE-A
ATTN: DAEN-ZCE-O (2)

US Army Engineer District
New York 10007
ATTN: Chief, Design Br
Philadelphia 19106
ATTN: Chief, NAFEN-E
Baltimore 21203
ATTN: Chief, Engr Div
Norfolk 23510
ATTN: Chief, MAEN-O
Huntington 25721
ATTN: Chief, ORMED
Wilmington 28401
ATTN: Chief, SAMEN-O
Savannah 31402
ATTN: Chief, SASAS-L
Mobile 36628
ATTN: Chief, SAMEN-D
Louisville 40201
ATTN: Chief, Engr Div
St. Paul 55101
ATTN: Chief, ED-O
Chicago 60604
ATTN: Chief, MCCPE-PES
Rock Island 61201
ATTN: Chief, Engr Div
St. Louis 63101
ATTN: Chief, ED-O
Omaha 68102
ATTN: Chief, Engr Div

New Orleans 70160
ATTN: Chief, LMED-OG
Little Rock 72203
ATTN: Chief, Engr Div
Tulsa 74102
ATTN: Chief, Engr Div
Ft. Worth 76102 (3)
ATTN: Chief, SWPED-O
San Francisco 94105
ATTN: Chief, Engr Div
Sacramento 95814
ATTN: Chief, SPKED-O
Far East 96301
ATTN: Chief, Engr Div
Seattle 98124
ATTN: Chief, EN-DB-ST
Walla Walla 99362
ATTN: Chief, Engr Div
Alaska 99501
ATTN: Chief, WPASA-R

US Army Engineer Division
New England 02154
ATTN: Chief, MEDED-T
North Atlantic 10007
ATTN: Chief, MAEN-T
Middle East (Rear) 22601
ATTN: Chief, MEDED-T
South Atlantic 30303
ATTN: Chief, SAGEN-TS
Huntsville 35807
ATTN: Chief, MEDED-CS
ATTN: Chief, MEDED-SR
Ohio River 45201
ATTN: Chief, Engr Div
Missouri River 68101
ATTN: Chief, MEDED-T
Southwestern 75202
ATTN: Chief, SWDED-T
South Pacific 94111
ATTN: Chief, SPDED-TB
Pacific Ocean 96858
ATTN: Chief, Engr Div
North Pacific 97208

6th US Army 94129
ATTN: AFKC-EN

7th Army Combined Arms Trng. Cntr. 09407
ATTN: AETTH-MRD-EHD

Armament & Dev. Command 21005
ATTN: DRDAR-BLT

US Army Tank Command
ATTN: DRSTA-SP 48090

USA ARRAADCOM 07801
ATTN: DRDAR-LCA-OK

AMC 22333
ATTN: DRCPA-E
ATTN: DRCS-A

TRADOC
Ft. Monroe, VA 23651

Ft. Clayton, Canal Zone 34004
ATTN: DPAE

Ft. Detrick, MD 21701

Ft. Leavenworth, KS 66027
ATTN: ATZLCA-SA

Ft. McPherson, GA 30330 (2)

Ft. Monroe, VA 23651 (6)

Ft. Rucker, AL 36360 (2)

Aberdeen Proving Ground, MD 21005
ATTN: DRDAR-BLL
ATTN: STEAP-MT-E

Human Engineering Lab. 21005 (2)

USA-MES 39181

Army Environmental Hygiene Agency 21005

Naval Air Station 92135
ATTN: Code 661

NAVFAC 22332 (2)

Naval Air Systems Command 20360

US Naval Oceanographic Office 39522

Naval Surface Weapons Center 22485
ATTN: N-43

Naval Undersea Center, Code 401 92152 (2)

Bolling AFB, DC 20332
AF/LEEEU

Patrick AFB, FL 32925
ATTN: XRQ

US Army Missile Command
ATTN: MLRS AMCPM-ML-PT-T

Wright-Patterson AFB, OH 45433 (3)

Building Research Advisory Board 20418

Transportation Research Board 20418

Dept of Housing and Urban Development 20410

Dept of Transportation Library 20590

White Sands Missile Range
ATTN: STEWS-TE-LD

Federal Aviation Administration 20591

Federal Highway Administration 22201
Region 15

NASA 23365 (2)

National Bureau of Standards 20234

Office of Noise Abatement 20590
ATTN: Office of Secretary

USA Logistics Management Center 23801

Airports and Construction Services Dir
Ottawa, Ontario, Canada K1A 0N8

Division of Building Research
Ottawa, Ontario, Canada K1A 0R6

National Defense HQDA
Ottawa, Ontario, Canada K1A 0K2

103
+47
2-83